



2880 - High Res. 540TVL Dome



SPECIFICATION

	NTSC	PAL
Signal system	NTSC	PAL
Image system		
Imaging area	4.9mm x 3.7mm	
Image pickup device	1/3"-SONY CCD HQ1	
Effective pixels(HxV)	795(H) x 596(V)	811(H) x 508(V)
Electric		
Scanning system	2:1 Interlace V: 59.94Hz, H: 15.734KHz	
Sync system	Internal	
Horizontal resolution	540 TV lines	540 TV lines
Built-in lens	f=3.6mm, F2.0 fixed lens	
View angle	-	
Gamma correction	0.45	
Minimum illumination	0.5 lux(F2.0, AGC on, 10 IRE)	
S/N ratio	More than 50dB (AGC off)	
Gain control	Auto	
White balance	Auto trace white balance	
Electric shutter	Auto 1/ 50(60) to 1/100,000sec.	
BLC	Auto	
Video output	1Vpp composite output, 75 ohm	
Power supply		
Power requirement	DC12V	
Power consumption	1.8W (max.)	
Environment		
Operating temperature	-10 C ~ 50 C	
Operating humidity	30% ~ 90% RH	
Storage temperature	-20 C ~ 60 C	
Mechanism		
Dimensions(oxH)	112(DIA) x 70(H) mm (4.41" x 2.76")	
Weight	220g approx.	