

ST-4MVP Standalone DVR



SPECIFICATION

MODEL NO.

Video System
Video Compression Format
Video Input (Composite video signal 1 Vp-p 75? BNC)
Audio Input / Output
Maximum Recording Rate
Recording Rate
Recording Rate
Image Quality Setting
Hard Disk Storage
Quick Search
SATA Interface
VGA Interface
Recording Mode
Multiplex Operation
USB Mouse Control
Motion Detection Area
Motion Detection Sensitivity
Pre-alarm Recording
Backup Device
Web Transmitting Compression Format
Ethernet

Web Interface

Network Protocol
Remote Independent Operation
Event Notification
IR Remote Control
Mobile Surveillance
Picture Zoom
PTZ Control
Alarm I/O
Key Lock (Password Protection)
User Level
Video Loss Detection
Camera Title
Video Adjustable
Date Display Format
Daylight Saving
Power Source ($\pm 10\%$)
Power Consumption ($\pm 10\%$)
Operating Temperature
Dimensions (mm)**
System Recovery

VC-SYS-4WEBMVP

NTSC / PAL (auto detection)
H.264
Main Monitor Output: for stable display
4 audio inputs, 1 audio output (Mono)
[FRAME] 704x480 pixels with 30 IPS <NTSC> / 704x576 pixels with 25 IPS <PAL>
[FIELD] 704x240 pixels with 60 IPS <NTSC> / 704x288 pixels with 50 IPS <PAL>
[CIF] 352x240 pixels with 120 IPS <NTSC> / 352x288 pixels with 100 IPS <PAL>
SUPER BEST / BEST / HIGH / NORMAL
Accommodates 1 SATA HDD (capacity up to 2TB)
Time / Motion / Alarm search mode
Built-in
Built-in
Manual / Timer / Motion / Alarm / Remote
Live display / record / playback / backup / network operations
YES
16 x 12 grids per channel
3 adjustable parameters for accurate detection
YES
USB 2.0 flash drive / Network
H.264
10/100 Base-T. Supports remote control and live view via Ethernet
"Licensed software "Video Viewer" / Internet Explorer, Mozilla Firefox or Google
Chrome web browser / QuickTime player (5 users access simultaneously)
*Operating System: Windows 7 / Vista / XP / 2000"
TCP/IP, PPPOE, DHCP and DDNS
YES
By FTP & E-Mail
YES (IR receiver built-in)
YES (Including iPhone & BlackBerry)
2X digital zoom
YES
4 inputs, 1 output
YES
Administrator & Operator
YES
Supports up to 6 letters
Hue / Saturation / Contrast / Brightness
YY/MM/DD, DD/MM/YY & MM/DD/YY
YES
DC 19V
<42 W
10°C ~ 40°C(50°F~104°F)
343(W) x 59(H) x 223(D)
System auto recovery after power failure